

DC to DC Switch Power Supply 25 Watts



Applications

- LED Signage
- LED Architectural Lighting
- LED Industrial Lighting
- LED Channel Letter
- LED General Lighting

LD1026 Series

- 25 Watts
- DC to DC Switch
- Power Supply

Features



DC Output with Constant Current, Outdoor or Indoor use
 Waterproof Design - IP66, NEMA3 for Dry, Damp Location
 Convection Cooled in plastic housing Parallel Operation (Constant Current)
 Meet FCC and CE, Three Years Warranty

Specifications

Input Range : 10 – 30 VDC / 3.5A	MTBF(@25°C) : >100,000 Hours, MIL-217F
Efficiency : 85% Typical	EMC meet : FCC , CE
Protection : OPP,SCP - Auto Recovery	Dimension : 85(L),35(W),23(H) mm +/- 0.5mm
Operation Temp. : -30°C ~ +50°C, Tc : 70°C	Weight : 120 Grams Typical
Storage Temp. : -40°C ~ +85°C	

Model Listing

Model	DC Output(V) Forward Voltage	DC Output Constant Current	Watts Max.
LD1026-36-C0700	2 ~ 36V	700mA ± 5%	25W
LD1026-24-C1050	2 ~ 24V	1050mA ± 5%	25W
LD1026-18-C1400	2 ~ 18V	1400mA ± 5%	25W
LD1026-12-C2100	2 ~ 12V	2100mA ± 5%	25W

Mechanical Drawing

